






LED TUBE with Sensor Microwave						
NO.	Model No. / Product Picture	Product Specification	Color Temperature	Lumens	Lamp Size	Net weight
1	 ITF17	1.Watt : 7W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	700lm	φ26mm × 300mm(H)	120g ±5%
2	 ITF26	1.Watt : 9W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	900lm	φ26mm × 600mm(H)	160g ±5%
3	 ITF23	1.Watt : 14W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	1400lm	φ26mm × 900mm(H)	210g ±5%
4	 ITF25	1.Watt : 18W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	1800lm	6mm × 1200mm(H)	260g ±5%
5	 ITF523	1.Watt : 23W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	2300lm	φ26mm × 1500mm(H)	310g ±5%

LED TUBE with Sensor Microwave						
NO.	Model No. / Product Picture	Product Specification	Color Temperature	Lumens	Lamp Size	Net weight
6	 ITF628	1.Watt : 28W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	2800lm	φ26mm × 1800mm(H)	360g ±5%
7	 ITF840	1.Watt : 40W 2.Input Voltage: AC100 ~ 240V 3.Operating Frequency: 50 ~ 60Hz 4.Power Factor: >0.85 5.Power Efficiency: 85% ±1 % 6.View Angle: 120°±10° 7.Color Rendering Index: >80@CW / >75@WW 8.Life Time: >10,000 hrs 9.Operating Tem: -20 ~ 60℃ 10.Warranty: 1 YRS	3000K(WW) 6000K(CW)	4000lm	φ26mm × 1800mm(H)	600g ±5%