








Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA601 series						
	PA601A	MAGNETIC MOUNT DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601B	MAGNETIC MOUNT DOME BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601D	MAGNETIC MOUNT DOME BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601E	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601F	MAGNETIC MOUNT DOME BEACON . 10 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601G	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601H	MAGNETIC MOUNT DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601I	MAGNETIC MOUNT DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601J	MAGNETIC MOUNT DOME BEACON . 10 SMD5050 intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601L	MAGNETIC MOUNT DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601M	MAGNETIC MOUNT DOME BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM
	PA601O	MAGNETIC MOUNT DOME BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 60*26*39CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA602 series						
	PA602A	MAGNETIC MOUNT DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602B	MAGNETIC MOUNT DOME BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602D	MAGNETIC MOUNT DOME BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602E	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602F	MAGNETIC MOUNT DOME BEACON . 10 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602G	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602H	MAGNETIC MOUNT DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602I	MAGNETIC MOUNT DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602J	MAGNETIC MOUNT DOME BEACON . 10 SMD5050 intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602L	MAGNETIC MOUNT DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602M	MAGNETIC MOUNT DOME BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA602O	MAGNETIC MOUNT DOME BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA603 series						
	PA603A	MAGNETIC MOUNT DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603B	MAGNETIC MOUNT DOME BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603D	MAGNETIC MOUNT DOME BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603E	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603F	MAGNETIC MOUNT DOME BEACON . 10 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603G	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA603H	MAGNETIC MOUNT DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603I	MAGNETIC MOUNT DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603J	MAGNETIC MOUNT DOME BEACON . 10 SMD5050 intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA603L	MAGNETIC MOUNT DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA603M	MAGNETIC MOUNT DOME BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA603O	MAGNETIC MOUNT DOME BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA604 series						
	PA604A	MAGNETIC MOUNT DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604B	MAGNETIC MOUNT DOME BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604D	MAGNETIC MOUNT DOME BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604E	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604F	MAGNETIC MOUNT DOME BEACON . 10 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604G	MAGNETIC MOUNT DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA604H	MAGNETIC MOUNT DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604I	MAGNETIC MOUNT DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604J	MAGNETIC MOUNT DOME BEACON . 10 SMD5050 intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 56*28*40CM
	PA604L	MAGNETIC MOUNT DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA604M	MAGNETIC MOUNT DOME BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM
	PA604O	MAGNETIC MOUNT DOME BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 44*28*39CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA605 series						
	PA605A	MAGNETIC MOUNT DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605B	MAGNETIC MOUNT DOME BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605C	MAGNETIC MOUNT DOME BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605D	MAGNETIC MOUNT DOME BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605H	MAGNETIC MOUNT DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605I	MAGNETIC MOUNT DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605K	MAGNETIC MOUNT DOME BEACON . Halogen rotation . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605L	MAGNETIC MOUNT DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM
	PA605M	MAGNETIC MOUNT DOME BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	24PCS/CTN CTN SIZE: 53*30.5*47.5CM







Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA606 series						
	PA606A	HIGH MAGNETIC MOUNT FLASHING BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606B	HIGH MAGNETIC MOUNT FLASHING BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606C	HIGH MAGNETIC MOUNT FLASHING BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606D	HIGH MAGNETIC MOUNT FLASHING BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606H	HIGH MAGNETIC MOUNT FLASHING BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606I	HIGH MAGNETIC MOUNT FLASHING BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM
	PA606K	HIGH MAGNETIC MOUNT FLASHING BEACON . Halogen rotation . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 49.5*33.5*43.5CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA607 series						
	PA607A	HEAVY DUTY MAGNETIC MOUNT BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607B	HEAVY DUTY MAGNETIC MOUNT BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607C	HEAVY DUTY MAGNETIC MOUNT BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607D	HEAVY DUTY MAGNETIC MOUNT BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607H	HEAVY DUTY MAGNETIC MOUNT BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607I	HEAVY DUTY MAGNETIC MOUNT BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607M	HEAVY DUTY MAGNETIC MOUNT BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607N	HEAVY DUTY MAGNETIC MOUNT BEACON . 8 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM
	PA607O	HEAVY DUTY MAGNETIC MOUNT BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*31CM





Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA608 series						
	PA608C	MAGNETIC MOUNT SUPER BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM
	PA608D	MAGNETIC MOUNT SUPER BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM
	PA608H	MAGNETIC MOUNT SUPER BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM
	PA608I	MAGNETIC MOUNT SUPER BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM
	PA608K	MAGNETIC MOUNT SUPER BEACON . Halogen rotation . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM
	PA608M	MAGNETIC MOUNT SUPER BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	12PCS/CTN CTN SIZE: 63*43*38CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA609 series						
	PA609D	MAGNETIC MOUNT BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA609H	MAGNETIC MOUNT BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA609I	MAGNETIC MOUNT BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA609K	MAGNETIC MOUNT BEACON . Halogen rotation . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
PA610 series						
	PA610B	MAGNETIC MOUNT BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610D	MAGNETIC MOUNT BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610E	MAGNETIC MOUNT BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610H	MAGNETIC MOUNT BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610I	MAGNETIC MOUNT BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610M	MAGNETIC MOUNT BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610N	MAGNETIC MOUNT BEACON . 8 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
	PA610O	MAGNETIC MOUNT BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM









Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA611 series						
	PA611K	MAGNETIC MOUNT BEACON . Halogen rotation . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 67*38*30CM
PA612 series						
	PA612C	MAGNETIC MOUNT OVAL BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN
	PA612D	MAGNETIC MOUNT OVAL BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN
	PA612H	MAGNETIC MOUNT OVAL BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN
	PA612I	MAGNETIC MOUNT OVAL BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A	12V/24V/12-24V optional	20PCS/CTN
	PA612M	MAGNETIC MOUNT OVAL BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA613 series						
	PA613A	MAGNETIC MOUNT BIG PLATTOP BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613B	MAGNETIC MOUNT BIG PLATTOP BEACON . Multiflash flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613C	MAGNETIC MOUNT BIG PLATTOP BEACON . 100 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613D	MAGNETIC MOUNT BIG PLATTOP BEACON . 72 LEDs 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613H	MAGNETIC MOUNT BIG PLATTOP BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613I	MAGNETIC MOUNT BIG PLATTOP BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613M	MAGNETIC MOUNT BIG PLATTOP BEACON . 8 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613N	MAGNETIC MOUNT BIG PLATTOP BEACON . 8 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM
	PA613O	MAGNETIC MOUNT BIG PLATTOP BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	20PCS/CTN CTN SIZE: 88*36*28CM

Warning Beacon Light

Photo	Model#	Description	LED Color	House Color	Voltage	Package
PA614 series						
	PA614A	MAGNETIC MOUNT MICRO DOME BEACON . Xenon single flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614B	MAGNETIC MOUNT MICRO DOME BEACON . Xenon Multiflash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	White	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614E	MAGNETIC MOUNT MICRO DOME BEACON . 26 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614F	MAGNETIC MOUNT MICRO DOME BEACON . 10 LEDs intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614H	MAGNETIC MOUNT MICRO DOME BEACON . 30 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614I	MAGNETIC MOUNT MICRO DOME BEACON . 40 SMD5050 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614J	MAGNETIC MOUNT MICRO DOME BEACON . 10 SMD5050 intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614L	MAGNETIC MOUNT MICRO DOME BEACON . 4 HIGH POWER LED 360° revolving flash / intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM
	PA614O	MAGNETIC MOUNT MICRO DOME BEACON . 9 HIGH POWER LED intermittent flash . DC 12V or dual voltage(12V/24V) . Meets IP56 protection standards . -30°C to + 50°C temperature range	R/B/A/W	R/B/A/W	12V/24V/12-24V optional	30PCS/CTN CTN SIZE: 72.5*30*33.5CM

Accessories for optional

12-24V dual voltage	Pls kindly let us know if you want to make the mini bar with 12/24V dual voltage, need to charge \$1/PC additional.
----------------------------	---

Note:
Payment term: TT 30% deposit in advance,70% balance against cargo ready photos
Delivery date: 7-10 days for sample order, 15-30 days for bulk order.
Trade term: EX-Factory