

Wattage	Part No.	Picture	LED	Specification	Packing Size	Inner Box	Gross Weight(KG/ Ctn.)	Net Weight ( KG/PCS )	PCS/Ctn	Exw Unit Price(USD)
20W	TR-PA8020(8D)		3535	Wattage: 20W LED type: Cree Voltage: 12-30V Intensity: 470LM Color Temp: 7960K Material: Alumi cover LENS: PC Frame: Alumi Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	20*10*10 Pair Pack	12	0.55	20	7.32
20W	TR-PA3220(6D)		5050	Wattage: 20W LED type: Cree Voltage: 12-30V Intensity: 362LM Color Temp: 6618K Material: Alumi cover LENS: PC Frame: Alumi Light Shape: Spot/Flood Life Span : 30000-50000Hrs	54*31*21	17.3*10.5*9.2 Pair Pack	15	0.35	40	7.32
27W	TR-PA6627(5D)		EPISTA( Frame can be chosen in Red or Black )	Wattage: 27W LED type: Epistar ( 9LED ) Voltage: 12-30V Intensity: 1620LM Color Temp: 6000K-6500K Material: Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	12.5*7.5*13.8 Pair Pack	13.5	0.60	20	9.76
48W	TR-PA7648(5D)		EPISTA( Frame can be chosen in Red or Black )	Wattage: 48W LED type: Epistar Voltage: 12-30V Intensity : 2880LM Color Temp: 6000K-6500K Material: Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	14*12*14 Pair Pack	13.5	0.60	20	10.17
18W	TR-PA1618(5D)		Epistar	Wattage: 18W LED type: Epistar Voltage: 12-30V Intensity: 1100LM Color Temp: 6000K-6500K Material: Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	54*36*21	17*10.5*7.5 Pair Pack	17.5	0.40	40	7.73
27W	TR-PA5527GQ(5D)	 	( Ring Color Options: Red, Yellow, Blue, Green )	Wattage: 27W LED type: Epistar Voltage: 12-30V Intensity: 1600LM Color Temp: 6000K-6500K Material: Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	14*12*14 Pair Pack	12	0.50	20	7.32
42W	TR-PA7642GQ(5D)	 	Epistar ( Ring Color Options: Red, Yellow, Blue, Green )	Wattage: 42W LED type: Epistar Voltage: 12-30V Intensity: 2500LM Color Temp: 6000K-6500K Material: Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	14*12*14 Pair Pack	14.5	0.65	20	7.73

48W	TR-PA7248GQ(SD)		Epistar ( Ring Color Options: Red, Yellow, Blue, Green )	Wattage: 48W LED type: Epistar Voltage: 12-30V Intensity:2800LM Color Temp: 6000K-6500K Material:Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	14*12*14 Pair Pack	13.5	0.60	20	8.54
12W	TR-PA8012 RGB		CREE ( Remote unit , RGB )	Wattage: 12W LED type: Cree Voltage: 12-30V Intensity:840LM Color Temp: 6000K-6500K Material:Alumi cover LENS: PC Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	20*10*10 Pair Pack	12	0.55	20	19.32
45W	TR-PA6645GQ		Epistar	Wattage: 45W LED type: Epistar Voltage: 10-30V Intensity:2700LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39*38*22	18*12.5*10	8.4	7.80	12	11.39
45W	TR-PA7045GQ		Epistar	Wattage: 45W LED type: Epistar Voltage: 10-30V Intensity:2750LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	38*37*37	20*17*12.5	8.8	8.64	12	12.00
15W	TR-PA4615		Epistar	Wattage: 15W LED type: Epistar Voltage: 10-30V Intensity:900LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	26*26*34	12*4.8*16	10.5	0.46	20	3.46
18W	TR-PA4618		Epistar	Wattage: 18W LED type: Epistar Voltage: 10-30V Intensity:1100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	26*26*34	12*4.8*16	10.3	0.45	20	3.66
24W	TR-PA4624	 	Epistar	Wattage: 24W LED type: Epistar Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	26*26*34	12*4.8*16	10.9	0.48	20	4.07
27W	TR-PA5527Thick	 	Epistar	Wattage: 27W LED type: Epistar Voltage: 10-30V Intensity:1600LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	26*26*34	12*4.8*16	10.5	0.50	20	3.66
	TR-PA5527 Middle Thickness Type	 	Epistar	Wattage: 27W LED type: Epistar Voltage: 10-30V Intensity:900LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	125*75*138	14.4	0.65	20	4.17

42W	TR-PA7642		Epistar	Wattage: 42W LED type: Epistar Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	125*75*138	17.6	0.81	20	6.92
48W	TR-PA7248Thick		3030	Wattage: 48W LED type: 3030 Voltage: 10-30V Intensity:2800LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	12.5*7.5*13.8	16.4	0.75	20	5.69
	TR-PA7248中厚款		Epistar	Wattage: 48W LED type: Epistar Voltage: 10-30V Intensity:2900LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	12.5*7.5*13.8	18.4	0.85	20	6.31
15W	TR-PA1615		Epistar	Wattage: 15W LED type: Epistar Voltage: 10-30V Intensity:900LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	36*30*25.5	17*5.3*7.6	15.7	0.47	30	4.07
18W	TR-PA1618 Lens Type		Epistar	Wattage: 18W LED type: Epistar Voltage: 10-30V Intensity : 1100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	36*30*25.5	17*5.3*7.6	14.2	0.42	30	3.25
	TR-PA1618 Reflectoer Type		Epistar	Wattage: 18W LED type: Epistar Voltage: 10-30V Intensity:1100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	36*30*25.5	17*5.3*7.6	14.2	0.42	30	3.25
10W	TR-PA3310		CREE	Wattage: 10W LED type: Cree Voltage: 10-30V Intensity:700LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	6.2	0.27	20	4.88
12W	TR-PA3312		Epistar	Wattage: 12W LED type: Epistar Voltage: 10-30V Intensity:700LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	7.4	0.33	20	4.27
10W	TR-PA2210		CREE	Wattage: 10W LED type: Cree Voltage: 10-30V Intensity:750LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	5.8	0.25	20	4.88

12W	TR-PA8012		CREE	Wattage: 12W LED type: Cree Voltage: 10-30V Intensity:850LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.62	20	5.08
12W	TR-PA8012FC		CREE	Wattage: 12W LED type: Cree Voltage: 10-30V Intensity:880LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.66	20	5.49
16W	TR-PA8016		CREE	Wattage: 16W LED type: Cree Voltage: 10-30V Intensity:1200LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.65	20	5.69
16W	TR-PA8016FC		CREE	Wattage: 16W LED type: Cree Voltage: 10-30V Intensity:1200LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.7	20	5.90
18w	TR-PA8018		CREE	Wattage: 18W LED type: Cree Voltage: 10-30V Intensity:1300LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.62	20	5.90
18W	TR-PA8018FC		CREE	Wattage: 18W LED type: Cree Voltage: 10-30V Intensity:1300LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.66	20	6.10
20W	TR-PA8020		CREE	Wattage: 20W LED type: Cree Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.65	20	6.31
20W	TR-PA8020FC		CREE	Wattage: 20W LED type: Cree Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.66	20	6.71
25W	TR-PA8025		CREE	Wattage: 25W LED type: Cree Voltage: 10-30V Intensity:1750LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.65	20	7.32

25W	TR-PA8025FC		CREE	Wattage: 25W LED type: Cree Voltage: 10-30V Intensity:2100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.66	20	7.73
30W	TR-PA8030		CREE	Wattage: 30W LED type: Cree Voltage: 10-30V Intensity:2100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	14.5	0.65	20	8.54
30W	TR-PA8030FC		CREE	Wattage: 30W LED type: Cree Voltage: 10-30V Intensity:2100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	10.5*9.7*12	15	0.66	20	9.15
20W	TR-PA1120		CREE	Wattage: 20W LED type: Cree Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	11.5	0.50	20	7.93
18W	TR-PA1118		Epistar	Wattage: 18W LED type: Cree Voltage: 10-30V Intensity:1300LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	11.2	0.52	20	4.07
15W	TR-PA1115		CREE	Wattage: 15W LED type: Cree Voltage: 10-30V Intensity:1100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	11.2	0.53	20	6.71
9W	TR-PA1109		CREE	Wattage: 9W LED type: Cree Voltage: 10-30V Intensity:650LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	11.5	0.53	20	4.68
40W	TR-PA7240		CREE	Wattage: 40W LED type: Cree Voltage: 10-30V Intensity:3000LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	12.5*7.5*13.8	18	0.83	20	13.22
48W	TR-PA7048		CREE	Wattage: 48W LED type: Cree Voltage: 10-30V Intensity:3400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	48*40*28	19.5*15.4*11.5	23.2	1.44	14	18.51

40W	TR-PA7040		CREE	Wattage: 40W LED type: Cree Voltage: 10-30V Intensity:3000LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	54*36*21	19.5*15.4*11.5	27.3	1.70	16	18.51
51W	TR-PA7051		Epistar	Wattage: 51W LED type: Epistar Voltage: 10-30V Intensity:3100LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	52*22.5*26	24.5*20.4*11.5	10	2.2	4	14.64
24W	TR-PA6524		Epistar	Wattage: 24W LED type: Epistar Voltage: 10-30V Intensity:1400LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	39.5*25.5*31	12.5*7.5*13.8	11.7	0.516	20	6.10
24W	TR-PA1124		Epistar	Wattage: 24W LED type: Epistar Voltage: 10-30V Intensity:1420LM Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs						5.90
20W	TR-PA3220		CREE	Wattage: 20W LED type: Cree Voltage: 10-30V Intensity:1400LM Color Temp: 2000K-2800K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	46.5*24.5*17	12*9*7.7	7.2	0.32	20	7.32
90W	TR-PA3390		CREE	Wattage: 90W LED type: Cree Intensity:6300LM Voltage: 10-30V Color Temp: 6000K-6500K Material:Alumi cover LENS: Acrylic Frame: Stainless Light Shape: Spot/Flood Life Span : 30000-50000Hrs	43*38.5*35	20*18*17	22.3	2.49	8	39.66