

彪雅有限公司 / Per-Accurate Incorporation

23586 新北市中和區中正路866-9號8樓







8F., No. 866-9, Zhongzheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)





TEL / 886-2-8221-7268

FAX / 886-2-8221-7269

Website / www.per-accurate.com , www.ledbulb.com.tw







Where Innovations Are Born **PA**[®]
PER-ACCURATE INC.


Photo	Model	Description	Receiver Parameters	NW
				gram
	PAW800	<ul style="list-style-type: none"> * Real time record 1296P full HD video or 1080P front+720P rear camera * 5.0-inch advanced IPS LCD. * Supports high capacity memory cards, TF up to 128GB. * LDW and FCW function * Loop recording function, automatically delete old files, record new files. * High resolution filter light wide angle 5 million pixels, &140 degrees wide angle 	<ul style="list-style-type: none"> * Video mode: Set video capture mode * Video quality: Select video recording quality * Film editing time: Film editing time * Flameout recording time: 0/5 seconds; 1/5/30/60 minutes * Sound recording: turn on/off * MIC sensitivity: adjust the volume of microphone * Scene selection: select different scene modes to record * Exposure adjustment: adjust brightness * White balace: adjust color balance 	860
	PAN800	<ul style="list-style-type: none"> * H.264 MOV image compression technology. * G-Sensor function, the impact of the car will be instantaneous impact, video files will be locked immediately. 		980
	PAW601	<ul style="list-style-type: none"> * APP compatible with Android car DVD navigation * Human voice alarm under abnormalities * Easy installation, rich functions in APP * Simultaneously show 4 tires' pressure and temperature * Support English, Simplified Chinese, Traditional Chinese * Tire match mode for rematch a new sensor easily * Tire exchange mode for easily rotate any two tires * Alarm for low/high pressure, high temperature * Adjustable high and low tire pressure alarm value 	<p>Receiver Technology Parameters</p> <ul style="list-style-type: none"> * Rated working voltage: DC5V * Static average operating current: ≤ 20mA * Receiving center frequency: 433.92MHZ * Receiving sensitivity: ≤-110dB * Operating temperature range: -20°C - +80°C * High/low pressure alarm value: 0-8Bar * High temperature alarm value: 60-90°C 	331
	PAN601	<ul style="list-style-type: none"> * Selectable tire pressure unit: Bar, Psi, Kpa, Kg * Selectable tire temperature unit: °C, °F <p>*APP download site: http://obd.syt-sz.com/android/T601.apk</p>		600
	PAW503	<ul style="list-style-type: none"> * Search and download APP SYTPMS in Google play or APP store for Android and ios smartphones * Monitor gets power from USB port * The pressure / temperature alarm value be adjusted 	<p>Receiver Parameters</p> <ul style="list-style-type: none"> * Rated operating voltage: DC5V * Static average operating current: ≤ 20mA * Receiving center frequency: 433.92MHZ * Receiving sensitivity: ≤-110dBm * Bluetooth transmission distance: > 8m * Operating temperature range: -20 to 80°C * Pressure alarm upper limit: 40.6Psi to 50.8Psi * Pressure alarm lower limit: 21.8Psi to 31.9Psi 	331
	PAN503	<ul style="list-style-type: none"> * Forget to take Mobile phone ;This system also has the human voice to emind * Tire pressure and temperature units arbitrary switching Global Universal * Visual, audible and vibration alarm 		601

	PAW502	<ul style="list-style-type: none"> * Search and download APP SYTTPMS in Google play or APP store for Android and ios smartphones * Wire fuze to get power * The pressure / temperature alarm value be adjusted * Forget to take Mobile phone ;This system also has the human voice to remind 	<p>Receiver Parameters</p> <ul style="list-style-type: none"> * Rated operating voltage: DC12V * Static average operating current: ≤ 20mA * Receiving center frequency: 433.92MHz * Receiving sensitivity: ≤-110dBm * Bluetooth transmission distance: > 8m * Operating temperature range: -20 to 80°C * Pressure alarm upper limit: 40.6Psi to 50.8Psi * Pressure alarm lower limit: 21.8Psi to 31.9Psi 	343
	PAN502	<ul style="list-style-type: none"> * Parking air leakage, open the door immediately remind * Tire pressure and temperature units arbitrary switching Global Universal * Visual, audible and vibration alarm 		612
	PAW501	<ul style="list-style-type: none"> * Search and download APP SYTTPMS in Google play or APP store for Android and ios smartphones * The pressure / temperature alarm value be adjusted * Forget to take Mobile phone ;This system also has the human voice to remind 	<p>OBD Receiver Parameters</p> <ul style="list-style-type: none"> * Rated operating voltage: DC12V * Static average operating current: ≤ 20mA * Receiving center frequency: 433.92MHz * Receiving sensitivity: ≤-110dBm * Bluetooth transmission distance: > 8m * Operating temperature range: -20 to 80°C * Pressure alarm upper limit: 40.6Psi to 50.8Psi * Pressure alarm lower limit: 21.8Psi to 31.9Psi 	331
	PAN501	<ul style="list-style-type: none"> * Parking air leakage, open the door immediately remind * Tire pressure and temperature units arbitrary switching Global Universal * Standard OBD plug and play, apply to most cars with four tires * Visual, audible and vibration alarm 		600
	PAW408	<ul style="list-style-type: none"> *Display spare tire data(Need to buy optional sensor) *Solar power and micro USB charging *High definition colorful LCD display *Wireless transmission design and randomly place the product *Super capacity battery, super long working life 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> *Work temperature range: -20°C~80°C *Storage temperature: -40°C~85°C *Signal reception frequency: 433.92MHz *Working humidity: 0~100% *Operating voltage: 12V *Alarm method: audio, visual flash *High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	591
	PAN408	<ul style="list-style-type: none"> *Screen enter sleep mode to save power when no any action for over 30s *Not necessary to change the sensor when rotating tire *Adjustable high and low tire pressure alarm value *Selectable temperature unit °C, °F *Selectable pressure unit Psi, Bar 		682

	PAW406	<ul style="list-style-type: none"> * Black and white screen saving power very much. * Normal usage for about two months once charged fully * Solar power and micro USB charging * Wireless transmission design and randomly place the product * Super capacity battery, super long working life 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> * Work temperature range: -20°C~80°C * Storage temperature: -40°C~85°C * Signal reception frequency: 433.92MHz * Working humidity: 0~100% 	638
	PAN406	<ul style="list-style-type: none"> * Screen enter sleep mode to save power when no any action for over 30s * Not necessary to change the sensor when rotating tire * Adjustable high and low tire pressure alarm value * Selectable pressure unit PSI, BAR 	<ul style="list-style-type: none"> * Operating voltage: 12V * Alarm method: audio, visual flash * High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	731
	PAW405	<ul style="list-style-type: none"> * Normal usage for about two months once charged fully * Solar power and micro USB charging * High definition colorful LCD display * Wireless transmission design and randomly place the product * Super capacity battery, super long working life 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> * Work temperature range: -20°C~80°C * Storage temperature: -40°C~85°C * Signal reception frequency: 433.92MHz * Working humidity: 0~100% 	633
	PAN405	<ul style="list-style-type: none"> * Screen enter sleep mode to save power when no any action for over 30s * Not necessary to change the sensor when rotating tire * Adjustable high and low tire pressure alarm value * Selectable pressure unit PSI, BAR 	<ul style="list-style-type: none"> * Operating voltage: 12V * Alarm method: audio, visual flash * High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	726
	PAW403	<ul style="list-style-type: none"> * Simple display only tire pressure or temperature. * Solar power and micro USB charging * High definition colorful LCD display * Wireless transmission design and randomly place the product * Super capacity battery, super long working life 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> * Work temperature range: -20°C~80°C * Storage temperature: -40°C~85°C * Signal reception frequency: 433.92MHz * Working humidity: 0~100% 	589
	PAN403	<ul style="list-style-type: none"> * Screen enter sleep mode to save power when no any action for over 30s * Not necessary to change the sensor when rotating tire * Adjustable high and low tire pressure alarm value * Selectable pressure unit PSI, BAR * Black, white, carbon fiber and camo available. 	<ul style="list-style-type: none"> * Operating voltage: 12V * Alarm method: audio, visual flash * High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	681

	PAW401	<ul style="list-style-type: none"> * Black and white screen saving power very much. * Normal usage for two months once charged fully * Streamlined appearance design, elegant and generous * Solar power and micro USB charging * High definition LCD display * Wireless transmission design and randomly place the product 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> * Work temperature range: -20°C~80°C * Storage temperature: -40°C~85°C * Signal reception frequency: 433.92MHz * Working humidity: 0~100% * Operating voltage: 12V * High/low pressure alarm range: 14-94Psi(1-6.5Bar) * Alarm method: audio, visual flash 	458
	PAN401	<ul style="list-style-type: none"> * Super capacity battery, super long working life * Screen enter sleep mode to save power when no any action for over 30s * Not necessary to change the sensor when rotating tire * Adjustable high and low tire pressure alarm value * Selectable pressure unit PSI, BAR * Black, white, carbon fiber and camo solar monitor available. 		712
	PAW400	<ul style="list-style-type: none"> * Streamlined appearance design, elegant and generous * Solar power and micro USB charging * High definition colorful LCD display * Wireless transmission design and randomly place the product 	<p>Solar Receiver Parameter</p> <ul style="list-style-type: none"> * Work temperature range: -20°C~80°C * Storage temperature: -40°C~85°C * Signal reception frequency: 433.92MHz * Working humidity: 0~100% * Operating voltage: 12V * Alarm method: audio, visual flash * High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	453
	PAN400	<ul style="list-style-type: none"> * Super capacity battery, super long working life * Screen enter sleep mode to save power when no any action for over 30s * Not necessary to change the sensor when rotating tire * Adjustable high and low tire pressure alarm value * Selectable pressure unit PSI, BAR 		707
	PAW300	<ul style="list-style-type: none"> * Elegant and compact figuration * Cigarette lighter plug display design * Simultaneously show 4 tires' pressure or temperature. * Real-time monitor tires' pressure and temperature, ensuring driving safety. 	<p>Receiver Technology Parameters</p> <ul style="list-style-type: none"> * Rated working voltage: DC12V * Static average operating current: ≤ 20mA * Receiving center frequency: 433.92MHZ * Operating temperature range: -20°C - +80°C * High/low pressure alarm range: 14-94Psi(1-6.5Bar) 	328
	PAN300	<ul style="list-style-type: none"> * It will alert immediately when low/high pressure. * Adjustable high and low tire pressure alarm value. * Selectable tire pressure unit: Psi and Bar. * White, black, carbon fiber and camo available. 		583

	PAM200		<p>Receiver Technology Parameters</p> <ul style="list-style-type: none"> * Rated working voltage: DC 9-24V * Static average operating current: ≤ 40mA * Receiving center frequency: 433.92MHZ * Operating temperature range: -20°C - +105°C * High/low pressure alarm range: 14-190Psi(1-13Bar) 	1000
	PAW200	<ul style="list-style-type: none"> * Monitor pressure and temperature of tyres in real-time. * Circulates display temperature and pressure of 4 tyres by axle sequence. * Pressure high, pressure low, rapid leak, temperature high alarm(sound-light alarm) * Monitors up to 40 tires * Trailer exchangeable * Pressure unit: Bar、PSI optional * Temperature unit:°C、°F optional * Vehicle battery voltage monitoring * Universal serial communication(UART TTL) support * Installation : stickup or holder * Power supply: DC 10~24 V Micro USB port * Battery CR2050 lasts 2 year, replaceable 		1000
	PAN200		<p>Receiver Technology Parameters</p> <ul style="list-style-type: none"> * Rated working voltage: DC 9-24V * Static average operating current: ≤ 40mA * Receiving center frequency: 433.92MHZ * Operating temperature range: -20°C - +105°C * High/low pressure alarm range: 14-190Psi(1-13Bar) 	1000
	PAY200			1000
<p>External Sensor</p> 	PAWF	<ul style="list-style-type: none"> * Very small, light, elegant * Use USA Freescale chip for stable accurate signal * Panasonic battery CR1632 lasts 2 year, replaceable * Waterproof, dustproof and anti-corrosion * No need to do wheel balance 	<ul style="list-style-type: none"> * Operating temperature: -25 to 85°C * Pressure range: 0 to 116Psi (8Bar) * Pressure accuracy: ±1.5Psi (0.1Bar) * Temperature accuracy: ±3°C * Transmission power: <10dBm * Transmission frequency: 433.92MHz * Dimension: 17mm*15.5mm(Diameter*Height) * Battery life: 2 year * Battery model: CR1632(Replaceable battery) 	7
<p>External Sensor</p> 	PAW	<ul style="list-style-type: none"> * Use German Infineon chip for stable accurate signal * Panasonic battery CR1632 lasts 2 year, replaceable * Waterproof, dustproof and anti-corrosion * No need to do wheel balance 	<ul style="list-style-type: none"> * Operating temperature: -25 to 85°C * Pressure range: 0 to 116Psi (8Bar) * Pressure accuracy: ±1.5Psi (0.1Bar) * Temperature accuracy: ±3°C * Transmission power: <10dBm * Transmission frequency: 433.92MHz * Dimension: 20mm*17mm (Diameter*Height) * Battery life: 2 year * Battery model: CR1632(Replaceable battery) 	10

	<p>PAN</p>	<ul style="list-style-type: none"> * Use German Infineon chip for stable accurate signal * Japan Maxell Battery last 5 years and non-change * Waterproof, dustproof, high temperature resistance and anti-corrosion * Adjustable angle of the black part to fit the hub * Need to install by technician, and do wheel balance * Convenient air inflation 	<ul style="list-style-type: none"> * Operating temperature: -40 to 125°C * Pressure range: 0 to 116Psi (8Bar) * Pressure accuracy: ±1.5Psi (0.1Bar) * Temperature accuracy: ±3°C * Transmission power: <10dBm * Transmission frequency: 433.92MHz * Dimension: 70*54.5*24mm (Length*Width*Height) * Battery life: 5 years (Non-replaceable battery) 	<p>38</p>
<p>Remarks:</p> <ol style="list-style-type: none"> 1. Every receiver matches with four sensors. 36 sets external type/carton; 20 sets internal type/carton. 2. MOQ: 100 sets/Model. Samples test order accept. 3. Quality Certification: CE, FCC, RoHS, NCC, ISO9001 4. Warranty: 1 year 5. Lead Time: Within 7 workdays for 100 sets. 6. Payment Terms: T/T 30% deposit, 70% balance before delivery. 7. OEM and ODM are available and you are welcome to be our agent or distributor in your country. 8. 1gram=0.035ounces 				